

## PRODUCT NAME ACS Gas Log Carbon & Soot Remover™

### MANUFACTURER

SaverSystems®  
Richmond, IN 47374  
800-860-6327  
Fax 765-935-4999  
www.chimneysaver.com

### DESCRIPTION

ACS Gas Log Carbon & Soot Remover is a non-toxic, environmentally safe spray-on cleaner that safely removes carbon and soot build-up from fireplace gas logs.

### USES

Use ACS Gas Log Carbon & Soot Remover to keep gas logs looking like new. Gas logs tend to accumulate carbon and soot. These spoil the appearance and are difficult to remove manually without damage to the surface. Deposits are due to one or more of the following causes: oxygen starvation (to achieve the "yellow flame" effect), the higher sulfur content of LP gas, misalignment of logs, inadequate air supply, or inadequate venting.

### BENEFITS

- Keeps gas logs clean
- Helps prevent black carbon accumulating in firebox
- Non-toxic
- Easy to use

### DIRECTIONS FOR USE

**Gas Logs:** Ignite the gas logs and burn for approximately 30 minutes to insure logs are hot. Shut off gas to logs. Spray ACS Gas Log Carbon & Soot Remover on logs while they are still hot. Carbon and soot will quickly disperse. Repeat as needed.

**Firebox:** While gas logs are still burning, liberally spray ACS Gas Log Carbon & Soot Remover on carbon build-up. Carbon and soot will quickly disperse. Repeat as needed.

### MAINTENANCE

Weekly application of ACS Gas Log Carbon & Soot Remover will keep fireplace gas logs and fireboxes clean.

**Limitations:** ACS Gas Log Carbon & Soot Remover is only effective when sprayed on hot logs. **Do not use on white logs, including 'birch' logs.** The chemicals in ACS Gas Log Carbon & Soot Remover will discolor white logs, turning them yellow. ACS Gas Log Carbon & Soot Remover is not effective on lightweight fiber logs and, therefore, should not be used on them. Carbon and Soot on unvented gas logs indicate unacceptable levels of carbon monoxide, requiring adjustment by a qualified technician. ACS Gas Log Carbon and Soot Remover can be used after unvented gas logs are properly adjusted to restore the appearance of the gas logs.

**Cleaning Spills:** Remove stains on hard surfaces with hydrogen peroxide to which is added a few drops of white vinegar. Apply to stains, and then blot up. Rinse textiles with water before product dries.

### CAUTIONS

**Keep out of reach of children.** Eye irritant. Avoid contact with eyes, mucous membranes & prolonged contact with skin.

**First Aid:** In case of eye contact, flush with plenty of water for at least fifteen minutes and get proper medical attention. In case of skin contact, wash as soon as possible with soap and water. In case of

ingestion, drink plenty of water, and contact a physician immediately.

### LIMITED WARRANTY

SaverSystems warrants this product to be free from defects for twelve months from date of purchase. Any claim must be made in writing, accompanied by proof of purchase. We will only be obligated to replace the product or refund the purchase price. There is no other express warranty. SaverSystems shall not be liable for direct or incidental, or consequential damages resulting from any breach of this warranty and fitness for use. Some states do not allow the exclusion of incidental or consequential damages, so the above warranty may not apply to you. This limited warranty gives you specific legal rights. You may also have other rights which vary from state to state.

### PACKAGING

ACS Gas Log Carbon & Soot Remover is packaged in 16 oz recyclable plastic spray bottles packed 12 per case.

### TRANSPORT AND STORAGE

ACS Gas Log Carbon & Soot Remover is not considered a hazardous material or substance under U.S. Department of Transportation (DOT) regulations. Store in a cool dry place inaccessible to children and animals. Keep from freezing.