

PRODUCT NAME

CrownSaver™
Crown Repair System

MANUFACTURER

SaverSystems®
Richmond, IN 47374
800-860-6327
Fax 765-935-4999
www.chimneysaver.com

DESCRIPTION

CrownSaver Crown Repair System is a blend of polymer hydrolic cements and modified polysiloxane (the active ingredient in ChimneySaver Water Repellent) specifically formulated for the repair of chimney crowns. CrownSaver is waterproof, durable, and easy to use. CrownSaver is a repair coating that can be installed with or without an underlayment of FormFoil™.

USES

CrownSaver can be used wherever a long-lasting, non-load bearing, cementitious repair coating is needed, such as chimney crowns, chimney corbels, the tops of masonry walls, including parapets, and stucco repair. Other uses include masonry window sills where bricks are laid in a soldier pattern at the base of windows.

CrownSaver can be used as a bonding mortar to replace badly spalled brick units or for parging over brick faces that may have spalled, if remaining brick is solid. Product can be used for crack repair, surface grouting and tuck pointing.

CrownSaver can be colored using small amounts of standard mortar dye. If dyes are used, transfer material to be colored from the original container into a clean mixing container. Before adding dye, let product stand uncovered for approximately 10 minutes to thicken. Add mortar dye one or two drops at a

time, and mix with trowel or paddle mixer and drill until desired color is reached.

BENEFITS

- Strong, long-term repair
- Waterproof barrier
- 10 year warranty
- Easy application

DIRECTIONS FOR USE

Preparation: Surface to be coated must be clean and structurally sound, not loose.

Mixing: Measure the surface area to be covered to determine the square footage (L x W). Do not deduct for tile liners. For each square foot to be covered, mix thoroughly one scoop of CrownSaver and three scoops of sand (scoop provided). Clean masonry or bagged sand is recommended. Add water sparingly and mix to the consistency of mortar. The mixture should be stiff but trowel easily.

APPLICATION

For use as repair coating: Apply a 1/2 inch bead of silicone sealant around each tile liner to form an expansion joint. Allow the sealant to slightly harden. Thoroughly dampen surface before applying. Trowel CrownSaver evenly over entire crown at a thickness of 1/4 inch minimum to 2 inches maximum. Surface misting with water may be needed for smooth troweling. When CrownSaver begins to set, smooth lightly with a masonry finish brush to remove trowel marks.

For use over FormFoil: Thoroughly wet FormFoil with water. Trowel CrownSaver evenly over FormFoil at a thickness of 1/4 inch to 1/2 inch. Mist with water and smooth lightly with a masonry finish brush to remove trowel marks.

Coverage: Contents will cover approximately 30 square feet at 1/2 inch when properly mixed.

Weather conditions: CrownSaver should not be applied at temperatures below 40°F or when temperatures are predicted to fall below 40°F within six hours after application. If rain is expected within four hours after the application, care should be taken to cover the repaired crown.

Clean-up: Tools should be cleaned with water before hardening occurs.

CAUTIONS

Keep out of reach of children. Contains CEMENTS. Avoid prolonged contact with skin. Wash thoroughly after handling. While handling this product, use goggles and gloves, as well as a NIOSH/MSHA approved respirator. (See your safety equipment supplier). Injurious to eyes. Causes skin irritation.

First Aid: External: Wash skin with soap and water. Eye contact: Immediately flush with clean water for fifteen minutes. Consult a physician. For additional information, consult the Material Safety Data Sheet for this product.

LIMITED WARRANTY

SaverSystems warrants CrownSaver repair coating against cracks caused by shrinkage of material for a period of ten years. This warranty is in effect if the product is professionally applied to a residential chimney according to printed label directions. This warranty does not cover improper mixing, incorrect application, or other factors beyond the manufacturer's control. If CrownSaver fails to perform as specified above, the purchaser must give prompt written notice of the defect to the professional from whom the product was purchased. Upon approval, SaverSystems will

furnish, without charge, enough CrownSaver repair coating to correct the condition as the sole remedy. This warranty does not include labor or cost of labor for the application of CrownSaver. SaverSystems shall not be liable for direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so the above exclusion may not apply to you. This warranty

gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

CrownSaver is available in five gallon recyclable plastic containers.

TRANSPORT AND STORAGE

CrownSaver is not considered a hazardous material or sub-

stance under U.S. Department of Transportation (DOT) regulations. Product should be kept dry. Store in cool dry place.

